

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Issue date: 06/01/2023 Revision date: 26/10/2023 Version: 1.1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Rebel BGE

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Use of the substance/mixture : For research and development use only.

Function or use category : Laboratory chemicals

1.2.2. Uses advised against

Restrictions on use : Not for use in diagnostic procedures.

1.3. Details of the supplier of the safety data sheet

Manufacturer

908 Devices 645 Summer St 02210 Boston, MA USA

T 1 (857) 254 - 1500 908devices.com

1.4. Emergency telephone number

Emergency number : 1 (844) 908 - 4357

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 2 H225
Skin Irrit. 2 H315
Eye Irrit. 2 H319
STOT SE 3 H336
Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :





GHS02

GHS07

Signal word (CLP) : Danger

Contains : Isopropyl alcohol; Formic acid

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H315 - Causes skin irritation.
H319 - Causes serious eye irritation.

H336 - May cause drowsiness or dizziness.

Precautionary statements (CLP) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

P233 - Keep container tightly closed.

P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 - Wash hands, forearms and face thoroughly after handling.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P403+P235 - Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Other hazards which do not result in classification : Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Contains no PBT/vPvB substances ≥ 0.1% assessed in accordance with REACH Annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Isopropyl alcohol substance with national workplace exposure limit(s) (BE, FR, DE)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0	20 – 50	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Formic acid substance with national workplace exposure limit(s) (BE, FR, DE, IT, NL); substance with a Community workplace exposure limit (Note B)	CAS-No.: 64-18-6 EC-No.: 200-579-1 EC Index-No.: 607-001-00-0	< 4	Flam. Liq. 3, H226 Acute Tox. 4 (Oral), H302 (ATE=1100 mg/kg bodyweight) Acute Tox. 3 (Inhalation:vapour), H331 (ATE=7,85 mg/l/4h) Skin Corr. 1A, H314 Eye Dam. 1, H318

Specific concentration limits:		
Name Product identifier Specific concentration limits (%)		Specific concentration limits (%)
Formic acid	EC-No.: 200-579-1 EC Index-No.: 607-001-00-0	(2 ≤ C < 10) Skin Irrit. 2, H315 (2 ≤ C < 10) Eye Irrit. 2, H319 (10 ≤ C < 90) Skin Corr. 1B, H314 (90 ≤ C < 100) Skin Corr. 1A, H314

Note B:

Some substances (acids, bases, etc.) are placed on the market in aqueous solutions at various concentrations and, therefore, these solutions require different classification and labelling since the hazards vary at different concentrations. In Part 3 entries with Note B have a general designation of the following type: '... %'. In this case the supplier must state the percentage concentration of the solution on the label. Unless otherwise stated, it is assumed that the percentage concentration is calculated on a weight/weight basis.

Full text of H- and EUH-statements: see section 16

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation : If inhaled and if breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

First-aid measures after skin contact : If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower. Wash clothing before re-using. If skin irritation occurs: Get medical

advice/attention.

First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical

advice/attention.

First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an

unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause irritation to the respiratory tract. May cause drowsiness or dizziness.

Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the

skin.

Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking

and tear production, with marked redness and swelling of the conjunctiva.

Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and

diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Dry chemical powder. Alcohol-resistant foam. Carbon dioxide (CO2). Unsuitable extinguishing media : Do not use a solid water stream as it may scatter and spread fire.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapour. Products of combustion may include, and are not

limited to: oxides of carbon. Irritating vapours. Formaldehyde.

Explosion hazard : May form flammable/explosive vapour-air mixture. Heavier than air, vapours may travel long

distances along ground, ignite and flash back to source.

5.3. Advice for firefighters

Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool closed

containers exposed to fire with water spray. Prevent runoff from entering water courses,

sewers and basements.

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory

protection (SCBA).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry

to unnecessary and unprotected personnel. Use special care to avoid static electric charges. Remove all sources of ignition.

-----**g**------

No additional information available

6.1.1. For non-emergency personnel

6.1.2. For emergency responders

No additional information available

26/10/2023 (Revision date) EN (English) 3/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

6.2. Environmental precautions

Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment

: Stop leak if safe to do so. Remove ignition sources. Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.

Methods for cleaning up

: Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed

- : Handle empty containers with care because residual vapours are flammable.
- Precautions for safe handling
- : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid contact with skin and eyes. Avoid breathing

dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area.

Hygiene measures

: Take off immediately all contaminated clothing and wash it before reuse. Wash hands,

forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures Storage conditions

- : Proper grounding procedures to avoid static electricity should be followed.
- : Keep out of the reach of children. Keep container tightly closed. Do not store in unlabelled containers. Store in a dry, cool and well-ventilated place. Keep cool. Keep out of direct sunlight. Containers which are opened should be properly resealed and kept upright to prevent leakage. Protect from physical damage.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

opropyl alcohol (67-63-0)		
Belgium - Occupational Exposure Limits		
Local name	Alcool isopropylique # Isopropylalcohol	
OEL TWA	500 mg/m³	
OEL TWA	200 ppm	
OEL STEL	1000 mg/m³	
OEL STEL	400 ppm	
Regulatory reference Koninklijk besluit/Arrêté royal 11/05/2021		
France - Occupational Exposure Limits		
Local name Alcool isopropylique		
VLE (OEL C/STEL)	980 mg/m³	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

VLC (OEL CNSTEL) (pym) 400 pym Remark Valeurs recommandees/admises Regulatory reference Circularie du Ministère du travail (reft. NRS ED 984, 2016) Germany - Occupational Exposure Limits (TRGS 300) Propan-2-ol ACW (OEL TWA) [1] 500 mpm² (the risk of damage to the embryo or febus can be excluded when AGW and BCW values are observed) AGW (OEL TWA) [2] 200 ppm (the risk of damage to the embryo or febus can be excluded when AGW and BCW values are observed) Peak exposure limitation factor 2(1) Remark DFG - Senatakommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (WARK-Kommission), Y - Err Risko der Fruchtschädigung braucht net Erinahtung des Arbeitsplötzgertravers und des biologischen Grenzwertes (8GW) nicht befürchtet zur Werden vertrechten und Befürchtet zur Werden vertrechten und Beführtet zu werden vertrechten Schädigung braucht net Erinahtung des Arbeitsplötzgertravers und des biologischen Grenzwertes (8GW) nicht befürchtet zur Werden vertrechten und Beführtet zur werden vertrechte und Beführtet zur werden werden werden werden vertrechte Schädigung braucht net Erinahtung des Arbeitsplötzgertravers und des biologischen Grenzwertes (8GW) nicht beführtet zur Werden vertrechte zu und est biologischen Grenzwerte (8GW) nicht beführtet zu werden werden werden werden werden werden des biologischen Grenzwerte (8GW) nicht erinahtung des Arbeitsplötzgertravers und des biologischen Grenzwerte (8GW) nicht erinahtung des Arbeitsplötzgertravers und des biologischen Grenzwerte (8GW) nicht erinahtung des Arbeitsplötzgertravers und des biologischen Grenzwerte (8GW) nicht erinahtung des Arbeitsplötzgertravers	Isopropyl alcohol (67-63-0)		
Regulatory reference Circulaire du Ministère du travail (réf.: INRS ED 984, 2016) Germany - Occupational Exposure Limits (TRGS 903) AGW (OEL TWA) [1] So mg/m² (indicative limit) Peak exposure limitation factor 2(1) Remark (Des Propan-2-cl) AGW (Sel TWA) [2] So mg/m² (indicative limit) Peak exposure limitation factor 2(1) Remark (Des Propan-2-cl) Peak exposure limitation factor 2(1) Remark (Des Propan-2-cl) AGW (action of the mbryo or fetus can be excluded when AGW and BGW values are observed) Peak exposure limitation factor 2(1) Remark (Des Propan-2-cl) Begulatory reference Tracks exposure Limits (TRGS 903) Fermany - Biological limit values (TRGS 903) Formic acid (64-18-6) EU - Indicative Occupational Exposure Limits (DEL) OEL TWA 9 spm Deli Spill (1) Indicative Limits (TRGS 903) Formic - Occupational Exposure Limits OEL TWA 9 spm Deli STEL 10 spm Deli STEL 10 spm Deli STEL 10 spm Deli Spm Deli STEL 10 spm Deli Spm Deli STEL 10 spm Deli Spm Deli Stel TWA 9 spm Deli Spm Deli Stel TWA 9 spm Deli Stel TWA 9 spm Deli Stel TWA 9 spm Deli STEL 10 spm Deli STEL 10 spm Deli Stel TWA 9 spm Deli STEL 10 spm Deli Stel TWA 9 spm Deli Stel TWA 10 spm	VLE (OEL C/STEL) [ppm]	400 ppm	
Carmany - Occupational Exposure Limits (TRGS 90)	Remark	Valeurs recommandées/admises	
Local name Propan-2-ol S00 mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW (OEL TWA) [1] S00 mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Peak exposure limitation factor 200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Peak exposure limitation factor 2010 pmm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Peak exposure limitation factor 2010 pmm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Peak exposure limitation factor 2010 pmm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Peak exposure limitation factor 2010 pmm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Peak exposure limitation factor 2010 pmm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Peak exposure limitation factor 2010 pmm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Peak exposure limitation factor 2010 pmm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Peak pmm (DEL TWA) [1]	Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)	
AGW (OEL TWA) [1] 500 mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and EGW values are observed) AGW (OEL TWA) [2] 200 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and EGW values are observed) Peak exposure limitation factor 2(II) Remark DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtelt zu werden Regulatory reference	Germany - Occupational Exposure Limits (TRGS 90	00)	
BGW values are observed)	Local name	Propan-2-ol	
BGW values are observed	AGW (OEL TWA) [1]		
Remark BPG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden Regulatory reference Regulatory Biological limit values (TRGS 903) Local name Propan-2-ol Biological limit value 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling ti	AGW (OEL TWA) [2]		
MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Abeltsplätzgenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden Regulatory reference TRGS900 Gormany - Biological Iimit values (TRGS 903) Local name Propan-2-ol Biological Iimit value 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift Regulatory reference TRGS 903 Formic acid (64-18-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 9 mg/m² IOEL TWA (ppm) 5 ppm Belgium - Occupational Exposure Limits OEL TWA 9.5 mg/m² OEL STEL 19 mg/m² OEL STEL 19 pm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m² (indicative limit) VME (OEL TWA) (ppm) 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 90) AGW (OEL TWA) [1] 9.5 mg/m² (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m² OEL TWA 9 mg/m² OEL TWA 9 mg/m² OEL TWA 9 ppm (the ris	Peak exposure limitation factor	2(II)	
Germany - Biological limit values (TRGS 903) Local name Propan-2-ol Biological limit value 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: while Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: while Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: while Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: while Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: while Sampling time: en	Remark	(MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu	
Local name Propan-2-ol Biological limit value 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift Regulatory reference TRGS 903 Formic acid (64-18-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 9 mg/m³ IOEL TWA 9 mg/m³ Belgium - Occupational Exposure Limits OEL TWA 9,5 mg/m³ OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 19 mg/m² OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 9 mg/m³ OEL TWA 9 pmg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	Regulatory reference	TRGS900	
Biological limit value 25 mg/l Parameter: Acetone - Medium: whole blood - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift 25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift Regulatory reference TRGS 903 Formic acid (64-18-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 9 mg/m³ IOEL TWA 9 mg/m³ Belgium - Occupational Exposure Limits OEL TWA 9,5 mg/m³ OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 19 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) 19 mg/m³ (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	Germany - Biological limit values (TRGS 903)		
25 mg/l Parameter: Acetone - Medium: urine - Sampling time: end of shift Regulatory reference TRGS 903 Formic acid (64-18-6) EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 9 mg/m³ IOEL TWA [ppm] 5 ppm Belgium - Occupational Exposure Limits OEL TWA 5 ppm OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 19 mg/m³ OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) ppm] 5 ppm (indicative limit) VME (OEL TWA) 9 mg/m³ (officiative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9.5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	Local name	Propan-2-ol	
EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 9 mg/m³ IOEL TWA [ppm] 5 ppm Belgium - Occupational Exposure Limits OEL TWA 9,5 mg/m³ OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) 9 pmg/m³ (indicative limit) Germany - Occupational Exposure Limits (TRGS 90) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	Biological limit value		
EU - Indicative Occupational Exposure Limit (IOEL) IOEL TWA 9 mg/m³ IOEL TWA [ppm] 5 ppm Belgium - Occupational Exposure Limits OEL TWA 9,5 mg/m³ OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 9 mg/m³ OEL TWA 5 ppm	Regulatory reference	TRGS 903	
IOEL TWA [ppm] 5 ppm Belgium - Occupational Exposure Limits OEL TWA 9,5 mg/m³ OEL TWA 9,5 mg/m³ OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) 9 mg/m³ (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 9 pm/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	Formic acid (64-18-6)		
IOEL TWA [ppm] 5 ppm Belgium - Occupational Exposure Limits OEL TWA 9,5 mg/m³ OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	EU - Indicative Occupational Exposure Limit (IOEL)		
Belgium - Occupational Exposure Limits OEL TWA 9,5 mg/m³ OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 9 pmg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	IOEL TWA	9 mg/m³	
OEL TWA 9,5 mg/m³ OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 9 pmg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	IOEL TWA [ppm]	5 ppm	
OEL TWA 5 ppm OEL STEL 19 mg/m³ OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	Belgium - Occupational Exposure Limits		
OEL STEL 19 mg/m³ OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	OEL TWA	9,5 mg/m³	
OEL STEL 10 ppm France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	OEL TWA	5 ppm	
France - Occupational Exposure Limits VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	OEL STEL	19 mg/m³	
VME (OEL TWA) 9 mg/m³ (indicative limit) VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	OEL STEL	10 ppm	
VME (OEL TWA) [ppm] 5 ppm (indicative limit) Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	France - Occupational Exposure Limits		
Germany - Occupational Exposure Limits (TRGS 900) AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	VME (OEL TWA)	9 mg/m³ (indicative limit)	
AGW (OEL TWA) [1] 9,5 mg/m³ (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	VME (OEL TWA) [ppm]	5 ppm (indicative limit)	
BGW values are observed) AGW (OEL TWA) [2] 5 ppm (the risk of damage to the embryo or fetus can be excluded when AGW and BGW values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	Germany - Occupational Exposure Limits (TRGS 90	00)	
values are observed) Italy - Occupational Exposure Limits OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	AGW (OEL TWA) [1]		
OEL TWA 9 mg/m³ OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	AGW (OEL TWA) [2]		
OEL TWA 5 ppm Netherlands - Occupational Exposure Limits	Italy - Occupational Exposure Limits		
Netherlands - Occupational Exposure Limits	OEL TWA	9 mg/m³	
	OEL TWA	5 ppm	
TGG-15min (OEL STEL) 5 mg/m³	Netherlands - Occupational Exposure Limits		
	TGG-15min (OEL STEL)	5 mg/m³	

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Formic acid (64-18-6)	
TGG-15min (OEL STEL) [ppm]	2,7 ppm

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Consult the relevant monitoring standards for the region.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

8.2.2. Personal protection equipment

8.2.2.1. Eye and face protection

Eye protection:

Safety eyewear complying with an approved standard such as the European Standard EN166 should be used when a risk assessment indicates this is necessary to avoid exposure to dusts. Contact lenses should not be worn

8.2.2.2. Skin protection

Skin and body protection:

Chemical resistant apron. Flame retardant and anti-static material recommended.

Hand protection:

Chemical resistant gloves (according to European standard NF ISO 374-1 or equivalent)

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

8.2.2.4. Thermal hazards

Thermal hazard protection:

Not required for normal conditions of use.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Clear, colourless liquid.

Colour : Colourless.
Odour : Slight; Alcohol-like.
Odour threshold : Not available

26/10/2023 (Revision date) EN (English) 6/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Melting point : Not available Freezing point : Not available : Not available

Boiling point : Refer to component values below Flammability : Highly flammable liquid and vapour.

Lower explosion limit : Not available Upper explosion limit : Not available

Flash point : Refer to component values below

Auto-ignition temperature: Not availableDecomposition temperature: Not availablepH: Not availableViscosity, kinematic: Not available

Solubility : Water: completely soluble

Partition coefficient n-octanol/water (Log Kow) : Not available

Vapour pressure : Refer to component values below

Vapour pressure at 50°C : Not available
Density : Not available
Relative density : Not available
Relative vapour density at 20°C : Not available
Particle characteristics : Not applicable

Isopropyl alcohol (67-63-0)	opropyl alcohol (67-63-0)	
Boiling point	82,3 °C (at 1 atm)	
Flash point	12 °C	
Auto-ignition temperature	399 °C	
Vapour pressure	42 hPa (at 20 °C)	

Formic acid (64-18-6)	
Boiling point	100,23 °C (at 1013.25 hPa)
Flash point	46,5 °C (closed cup)
Auto-ignition temperature	539 °C
Vapour pressure	170,7 hPa (at 50 °C)

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions. May form flammable/explosive vapour-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials. Sources of ignition. Direct sunlight.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.5. Incompatible materials

Isopropyl alcohol (67-63-0)

Strong oxidizing agents. Aluminium. Magnesium. This material may attack some forms of plastics, rubbers and coatings.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. May release flammable gases. Formaldehyde.

SECTION 11: Toxicological information

		and the second second					
10	11	1 Information	on hazard of	20000 20 6	defined in Reau	lation (EC) N	JA 1272/2002
		i. Illioillauoli	UII IIazaiu Li	สออยอ สอ เ	Jeillieu III Neuu	Iauon lecti	NU 12/2/2000

Acute toxicity (oral) : Not classified.

Acute toxicity (dermal) : Not classified.

Acute toxicity (inhalation) : Not classified.

LD50 oral rat	5840 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)	
LD50 dermal rabbit	4059 mg/kg	
LC50 inhalation rat	> 10000 ppm (Exposure time: 6 h)	
Formic acid (64-18-6)		
LD50 oral rat	1100 mg/kg	
LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)	
LC50 inhalation rat	7,85 mg/l/4h	
Skin correcion/irritation	· Causes skin irritation	

 Skin corrosion/irritation
 : Causes skin irritation.

 Serious eye damage/irritation
 : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified.

Additional information : Based on available data, the classification criteria are not met.

Germ cell mutagenicity : Not classified.

Additional information : Based on available data, the classification criteria are not met.

Carcinogenicity : Not classified.

Additional information : Based on available data, the classification criteria are not met.

Isopropyl alcohol (67-63-0)		
IARC group	3 - Not classifiable	
Formic acid (64-18-6)		

NOAEL (chronic, oral, animal/male, 2 years)	400 mg/kg bodyweight Animal: mouse, Animal sex: male, Guideline: OECD Guideline 453
	(Combined Chronic Toxicity / Carcinogenicity Studies), Remarks on results: other:Effect
	type: toxicity (migrated information)

Reproductive toxicity : Not classified.

Additional information : Based on available data, the classification criteria are not met.

STOT-single exposure : May cause drowsiness or dizziness.

Isopropyl alcohol (67-63-0)	
STOT-single exposure	May cause drowsiness or dizziness.
	Not classified. Based on available data, the classification criteria are not met.

Additional information :	Based on available data, the classification criteria are not met.
Formic acid (64-18-6)	
LOAEL (oral, rat, 90 days)	2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
NOAEL (oral, rat, 90 days)	400 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Formic acid (64-18-6)	
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0,244 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
	Not classified. Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

Other information : Likely routes of exposure: ingestion, inhalation, skin and eye

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general

: May cause long-term adverse effects in the aquatic environment.

Hazardous to the aquatic environment, short-term

acute

: Not classified.

Hazardous to the aquatic environment, long–term $% \left(-1\right) =-1$

(chronic)

(unonic)		
Isopropyl alcohol (67-63-0)		
LC50 - Fish [1] 10000 mg/l Test organisms (species): Pimephales promelas		
LC50 - Fish [2] 9640 mg/l Test organisms (species): Pimephales promelas		
EC50 - Crustacea [1] 13299 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
EC50 72h - Algae [1] > 1000 mg/l (Species: Desmodesmus subspicatus)		
EC50 96h - Algae [1]	> 1000 mg/l (Species: Desmodesmus subspicatus)	
Formic acid (64-18-6)		
LC50 - Fish [1]	130 mg/l Test organisms (species): Danio rerio (previous name: Brachydanio rerio)	
EC50 - Crustacea [1] 120 mg/l (Exposure time: 48 h - Species: Daphnia magna)		
	i	

	2000 - 1 1311 [1]	100 mg/1 rest organisms (species). Danie rene (previous name. Brachydaine rene)	
EC50 - Crustacea [1] 120 mg/l (Exposure time: 48 h - Species: Daphnia magna)		120 mg/l (Exposure time: 48 h - Species: Daphnia magna)	
EC50 - Crustacea [2] 138 – 165,6 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])		138 – 165,6 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])	
EC50 72h - Algae [1] 26,9 mg/l (Species: Desmodesmus subspicatus)		26,9 mg/l (Species: Desmodesmus subspicatus)	
EC50 96h - Algae [1] 25 mg/l (Species: Desmodesmus subspicatus)		25 mg/l (Species: Desmodesmus subspicatus)	
LOEC (chronic) > 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'		> 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	
	NOEC (chronic)	≥ 100 mg/l Test organisms (species): Daphnia magna Duration: '21 d'	

12.2. Persistence and degradability

Rebel BGE	
Persistence and degradability	Readily biodegradable.

12.3. Bioaccumulative potential

Rebel BGE	
Bioaccumulative potential	Not expected to acummulate.

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Isopropyl alcohol (67-63-0)	
Partition coefficient n-octanol/water 0,05 (at 25 °C)	
Formic acid (64-18-6)	
BCF - Fish [1]	(0.22 dimensionless)
Partition coefficient n-octanol/water	-1,9 (at 23 °C (at pH 5)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

Rebel BGE

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations

: Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimized wherever possible.

Additional information

: Handle empty containers with care because residual vapours are flammable.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

14.1. UN number or ID number

UN-No. (ADR) : UN 1219 UN-No. (IMDG) : UN 1219 UN-No. (IATA) : UN 1219

14.2. UN proper shipping name

Proper Shipping Name (ADR) : ISOPROPANOL SOLUTION Proper Shipping Name (IMDG) : ISOPROPANOL SOLUTION Proper Shipping Name (IATA) : Isopropanol Solution

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 3
Danger labels (ADR) : 3

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878



IMDG

Transport hazard class(es) (IMDG) : 3
Danger labels (IMDG) : 3



IATA

Transport hazard class(es) (IATA) : 3
Danger labels (IATA) : 3



14.4. Packing group

Packing group (ADR) : II
Packing group (IMDG) : II
Packing group (IATA) : II

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

Overland transport

Limited quantities (ADR) : 1I Excepted quantities (ADR) : E2

Orange plates :



Transport by sea

No data available

Air transport

No data available

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

REACH Annex XVII (Restriction List)

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no REACH candidate substance.

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

Belgium

Belgian National Regulations : Not determined.

France

Occupational diseases	
Code	Description
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). **Employment restrictions**

Observe restrictions according Act on the Protection of Young People in Employment

(JArbSchG)

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1).

Storage class (LGK, TRGS 510) : LGK 3 - Flammable liquids.

Hazardous Incident Ordinance (12. BlmSchV) : Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Italy

Italian National Regulations : Not determined.

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen : None of the components are listed SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed : None of the components are listed

SZW-lijst van reprotoxische stoffen -

Vruchtbaarheid

SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

26/10/2023 (Revision date) EN (English) 12/15

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Indication of changes			
Section	Changed item	Change	Comments
14	Transport information	Modified	V1.1
SDS	Name	Modified	V1.1

Abbreviations and acronyms:

°C – Degrees Celsius

°F - Degrees Fahrenheit

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road.

ACGIH - American Conference of Governmental Industrial Hygienists

ATE - Acute Toxicity Estimate

BCF - Bioconcentration Factor

BEI – Biological Exposure Index

CAS - Chemical Abstracts Service

CLP - Regulation (EC) No 1272/2008 on the Classification, Labeling and Packaging of substances and mixtures.

CMR - Carcinogen, Mutagen, Reproductive toxin

cP - centipoise (unit of dynamic viscosity)

cSt - centistokes (unit of kinematic viscosity)

DNEL - Derived No-effect Level

DMEL - Derived Minimal Effect Level

EC50 - Half maximal effective concentration

ECHA – European Chemicals Agency

EC-No. - European Community number

EU - European Union

GHS - Globally Harmonized System of Classification and Labelling of Chemicals

h – Hours

IATA - International Air Transport Association

IC50 - Inhibition concentration

IDLH - Immediately Dangerous to Life or Health

IMDG – International Maritime Dangerous Goods

IOELV - Indicative Occupational Exposure Limit Value

KIFS - Swedish Chemicals Agency's (Keml's) Code of Statutes

kPa – kilopascal

Koc - Adsorption Coefficient

Kow - Octanol-Water Partition Coefficient

LC50 - Median Lethal Concentration

LD50 - Median Lethal Dose

LOAEL - Lowest Observed Adverse Effect level

mg/l - Milligram per liter

mg/kg - Milligram per kilogram

mg/m3 - Milligram per cubic meter

Min - Minutes

NIOSH - National Institute for Occupational Safety and Health

NOEC - No Observed Effect Concentration

NO(A)EL - No Observed (Adverse) Effect Level

N.O.S. - Not Otherwise Specified

OEL – Occupational Exposure Limit

PBT - Persistent, Bioaccumulative and Toxic

PCN - Poison Centre Notification

PNEC - Predicted No Effect Concentration

ppm - Parts per million

PVC - Polyvinyl chloride

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:

REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006

RID - European Agreement concerning the International Carriage of Dangerous Goods by Rail

SDS - Safety Data Sheet

STEL - Short Term Exposure Limit

STOT - Specific Target Organ Toxicity

SVHC – Substance of Very High Concern (CMR, vPvB, PBT)

TDI - Tolerable Daily Intake

TLV - Threshold Limit Value

TWA - Time Weighted Average

UFI - Unique Formulation Identifier

UN - United Nations

vPvB - Very Persistent and Very Bioaccumulative

WEL - Workplace Exposure Limit

WGK - Wassergefahrdungklasse - German water quality classification

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE

COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and

amending Regulation (EC) No 1907/2006.

Other information : None.

Prepared by : Nexreg Compliance Inc.

www.Nexreg.com



Full text of H- and EUH-statements:		
Acute Tox. 3 (Inhalation:vapour)	Acute toxicity (inhalation:vapour) Category 3	
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Liq. 2	Flammable liquids, Category 2	
Flam. Liq. 3	Flammable liquids, Category 3	
H225	Highly flammable liquid and vapour.	
H226	Flammable liquid and vapour.	
H302	Harmful if swallowed.	
H314	Causes severe skin burns and eye damage.	
H315	Causes skin irritation.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H331	Toxic if inhaled.	
H336	May cause drowsiness or dizziness.	
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	
Skin Irrit. 2	Skin corrosion/irritation, Category 2	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Flam. Liq. 2	H225	Calculation method

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Skin Irrit. 2	H315	Specific concentration limits
Eye Irrit. 2	H319	Specific concentration limits
STOT SE 3	H336	Calculation method

Safety Data Sheet (SDS), EU - Nexreg 2023

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.